SDPC Raceshop
5901 Spur 327
Lubbock, TX 79424
USA
(806) 798-4159

"Corrected Power and Torque" from test 416CARB-19.sfd

Test Information:

File name: 416CARB-19.sfd (SD-PM_T.cfa)
Data page: Corrected Power and Torque - 20 lines total
Tested on:

Test Description:

416 LS3 HEADS
APD CARB
APD BLACK WIDOW SPACER
JET-76 VP 113
TIMING-30
MAXIMA BREAK-IN OIL

EngSpd RPM	STPIPw CHp	STPITr Clb-ft	Oil_P 0-150p	Man_P InHg	CoolIn deg F	FuelP1 0-300p	FuelP2 0-300p	AirInT degF
5,500**	599.1	572.1	71.2	-0.7	154	7.5	7.0	60.5
5,600	608.8	571.0	71.0	-0.7	154	7.5	7.0	60.5
5,700	621.1	572.3	71.0	-0.7	154	7.5	7.0	60.5
5,800	633.6	573.7	71.0	-0.7	154	7.5	7.0	60.5
5,900	645.4	574.5	71.1	-0.7	154	7.5	7.0	60.5
6,000	656.5	574.7	71.1	-0.7	154	7.5	7.0	60.5
6,100	665.2	572.7	71.2	-0.7	154	7.6	7.0	60.5
6,200	671.1	568.5	71.2	-0.7	153	7.6	7.0	60.5
6,300	674.9	562.6	71.2	-0.7	153	7.5	7.0	60.5
6,400	674.5	553.5	71.0	-0.7	153	7.5	7.1	60.5
6,500	676.6	546.7	70.9	-0.7	153	7.5	7.1	60.5
6,600	680.6	541.6	70.7	-0.7	153	7.6	7.1	60.5
6,700	685.9	537.6	70.5	-0.7	152	7.6	7.0	60.5
6,800	691.1	533.8	70.3	-0.7	152	7.6	7.0	60.5
6,900	696.7	530.3	69.9	-0.7	152	7.6	7.0	60.5
7,000	700.9	525.9	69.4	-0.7	153	7.6	7.0	60.5
7,100	698.2	516.5	68.4	-0.7	153	7.6	7.0	60.5
7,200	695.7	507.5	67.7	-0.7	153	7.6	7.0	60.5
7,300	692.9	498.5	66.9	-0.7	153	7.6	7.0	60.5
7,400**	688.3	488.5	66.1	-0.7	153	7.5	7.0	60.5
Avg*								
6,450	***667.8***	***546.1***	***70.1***	***-0.7***	***153***	***7.6***	***7.0***	***60.5***
Max*								
7,400	***700.9***	***574.7***	***71.2***	***0.0***	***154***	***7.6***	***7.1***	***60.5***

©2007 SuperFlow Technologies Group. All Rights Reserved.